

C4050-Q4 UHF

Mobile Computer

CHAINWAY C4050-Q4 UHF is an Android rugged mobile computer. With its powerful quad-core processor and wireless connections such as 4G, Bluetooth and Wi-Fi, as well as comprehensive data capture options, including UHF RFID reading & writing, 1D/2D barcode scanning, infra-red and sensitive fingerprint scanning, you can find this easy-to-deploy device an exceptionally valuable helper for your workers to increase their efficiency and productivity. With its highly customizable ability, enterprises can deploy this device in many areas, including retail, logistics, express delivery, warehousing, energy and chemical industry, etc.



Most Powerful Application Performance

It adopts Android 5.1 OS, features the fast and powerful quad-core processor, together with 1/2GB of RAM, 8/16GB build-in flash storage, plus a SD card slot that can add up to 32GB of memory.



Fast Wireless Connectivity

Whether indoors or outdoors, C4050-Q4 UHF provides fast and stable network connectivity with a variety of options including 4G network, dual-band Wi-Fi. and Bluetooth.



Extensive Data Capture Functions

It can also be integrated with best-in class Zebra 1D/2D barcode scanning engine, sensitive fingerprint recognition and infrared functions. It allows users to choose data collection options as per industry need.



Superior UHF RFID Reading Capability

The C4050-Q4 UHF provides new levels of UHF RFID reading performance. It can be configured with class-leading R2000 UHF module or cost-effective UHF module, together with two kinds of high performance antenna options.



Powerful Battery

With the embedded 3200mAh main battery and the 5200mAh pistol battery, it enables non-stop operation over the full working day.



Highly Customizable

From a single function device to a fully featured enterprise mobile computer, this device delivers the best possible flexibility and diversity to satisfy a whole variety of application needs.

About Chainway

CHAINWAY®



















1D Barcode

2D Barcode

RFID

Fingerprint

Bluetooth



Physical Characteristics	
Triysical Chara	cteristics
Dimensions	213mm x 87mm x 151mm/ 8.39 x 3.43 x 5.94in
Weight	456g/ 16.08oz
Display	4" WVGA (480*800), 16.7M colors
Touch Panel	Rugged capacitive touch panel
Power	Main battery: Li-ion, 3200mAh
Power	Pistol battery: Li-ion, 5200mAh
Expansion Slot	1 PSAM, 1 SIM, 1 MicroSD(TF) slot
Interfaces	USB Micro-B
Audio	0.5W speaker, build-in microphone
Keypad	Numeric / Qwerty

Perfo	rms	nco
Perio	IIIIc	mce

Sensors

Option 1	CPU: Qualcomm 1.3 GHz quad-core
	RAM: 2GB
	ROM: 16GB
	CPU: Qualcomm 1 GHz quad-core
Option 2	RAM: 1GB
	ROM: 8GB
Expansion	Supports up to 32GB Micro SD card

Light Sensor, Proximity Sensor

Developing Environment

Operating System	Android 5.1
SDK	Chainway Software Development Kit
Language	Java
Tool	Eclipse / Android Studio

User Environment

Operating Temp.	14°F to 122°F / -10°C to 50°C
Storage Temp.	-40°F to 158°F / -40°C to 70°C
Humidity	5%RH - 95%RH non condensing
D C ''.	Multiple 1.2m drops to concrete across the
Drop Specification	operating temperature range
Tumble Specification	1000 x 0.5m/1.64ft falls at room temperature
Sealing	IP64

Communication

WLAN	IEEE802.11 a/b/g/n
WWAN(E)	2G: GPRS(900/1800MHz)
	3G: WCDMA B1 B8
	4G: FDD-LTE:B1 B3 B7 B8 B20
WWAN(N)	2G: GPRS(850/1900MHz)
	3G: WCDMA B1 B2 B5
	4G: FDD-LTE: B2 B4 B7 B17

	2G: GPRS(850/90	0/1800MHz)
WWAN(C)	3G: WCDMA: CDMA EVDD: TD-SCDMA:	B1 EVDD Rev.A800MHz B34, B39
	4G: TDD-LTE: FDD-LTE:	B38/B39/B40/B41 B1/B3
Bluetooth	Bluetooth 4.0	
GPS	GPS, AGPS	

Barcode Scanning (Optional)

1D Linear Scanner	
1D Laser / CCD	Symbol SE965
	UPC/EAN, Code128, Code39, Code93, Code11,
Symbologies	Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of
	5, Codabar, MSI, RSS, etc.
2D Imager Scanner	

2D CMOS Laser Scanner	Symbol SE4500
	PDF417, MicroPDF417, Composite, RSS, TLC-39,
	Datamatrix, QR code, Micro QR code, Aztec,

Symbologies MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX), etc.

RFID (Optional)

UHF	
Frequency	865MHz-868MHz / 920-925MHz / 902-928MHz
Protocol	EPC C1 GEN2 / ISO18000-6C
Antenna	Linear polarization (1.8dBi)
	Circular polarization (2.5dBi)
Power	1W (+10dBm to +30dBm)
	Option1(R2000), up to 4.5m
R/W ranges	Option2, up to 2m
	(Ranges depend on tags and environment)
Reading rates	200 tags/s

Biometric (Optional)

Functions	Enrollment, compare, deletion etc.
Sensor	TCS2SS
Sensor Type	Capacitive Sensor
Resolution	508DPI
Memory	1,000 PCS fingerprints

InfraRed (Optional)

, .	•
Wavelength	940nm
Frequency	38kHz
Range	> 4m

PSAM (Optional)

	Slots	2 PSAM slots(maximum)
	Protocol	ISO7816

 $Notice: Product specifications are subject to change without notice. / Version: C4050 Q4 \ UHF \ V1.1.0 \ / \ Update \ Date: 2017-03-15 \ Advisority of the product of th$

CHAINWAY®

Shenzhen Chainway Information Technology Co., Ltd



Accessories



AC Adapter



Snap-on



USB cable



Cradle





Fingerprint (Optional)

